



Congratulations on your purchase of the BOB Weather Shield. It is designed to provide your child protection from inclement weather. Proper installation and care will provide years of reliable service.

Before attempting to assemble or use your new Weather Shield, read and understand these instructions completely to insure proper assembly and operation. If you are unclear on any point, contact your dealer or BOB before use.

▲ WARNINGS ▲

This product is designed exclusively for use with BOB Revolution and Stroller Strides Strollers. It is not intended for use with other strollers or products.

The Weather Shield is made of a non-breathable material. To avoid danger of suffocation and excessive temperatures:

- Follow all assembly instructions.
- Make sure all vents are unobstructed, as shown in Fig.1.
- The Weather Shield is not designed to work with optional Infant Car Seat Adapter and car seat.
- Do not use Weather Shield when temperatures exceed 65°F/18°C. Use in higher temperatures can cause unsafe conditions inside the Weather Shield. Never leave child unattended.
- When not in use, keep out of reach of children.
- When the Weather Shield is used, the rear canopy flap must be repositioned as described below to insure proper airflow and avoid danger of suffocation.

INSTALLATION INSTRUCTIONS

1. Begin by locating the sun canopy and rear canopy flap into position to receive the Weather Shield.



A) Rotate sun canopy into position as shown in Fig. 2.

B) Pull canopy draw string in order to gather material under canopy. Sinch cord lock against canopy to hold material in place as shown in Fig. 3.

Very important: when the Weather Shield is used, the rear canopy flap must be repositioned as described below to insure proper airflow and avoid danger of suffocation.

C) Fold canopy flap forward and attach to Velcro on top of canopy as shown in Fig. 4. Note: Instructions on canopy flap also describe this critical step.

D) Inspect opening at back of stroller (see Fig. 5) to make sure the air passage space between top of seat back and canopy is unobstructed. We recommend reclining seat back slightly to optimize airflow (refer to Reclining Seat section of stroller Owner's Manual).

2. Position the Weather Shield on the stroller so that rear flap drapes over the back (between the handlebars) and the seam above the window is located over the front canopy support (see Fig. 6).

3. Stretch the elastic cord on each side under



Fig. 6 Shield placed on canopy




Fig. 7 Elastic under knob




Fig. 8 Front attachment



Fig. 9 Elastic under frame



Fig. 10 Shield placed on forward edge of canopy

the black shock knobs as shown in Fig. 7. There is an opening mid way up each side with silver fabric on both ends where the elastic cord is exposed.

4. Locate the looped ends of the elastic cord where they come out of the back flap of the Weather Shield. Each has a loop with a cord lock. One side at a time, attach the looped end of the elastic cord around the black shock knob (on the same side as loop) as shown in Fig. 7 (right side shown).

The cord locks allow the loop to be enlarged or reduced thereby adjusting the tension on the cord.

5. The front of the Weather Shield attaches to the lower frame at the nose of the stroller. Position lower air scoop so that it is centered left to right over the nose of the stroller. Now, hook the elastic edge of the shield under lip on the nose of the stroller as shown in Fig. 8.

6. Make sure the elastic edge of the Weather Shield is wrapped under the frame tube at the footwell area as shown in Fig. 9. After completion of Weather Shield installation, confirm back vents are aligned with space between top of seat back and canopy and opening is free of obstruction (see Fig. 1).

7. To place your child in the stroller, pull the front of the Weather Shield off the stroller then lift it up and over the forward edge of canopy (see Fig. 10). This will temporarily hold the Weather Shield out of your way while you



Fig. 11 Shield correctly installed

place your child into the seat.

8. Once your child is secured in the safety harness (refer to your stroller owner's manual for proper use of the safety harness system), release the Weather Shield from canopy and re-secure under the lip on the stroller nose (see Fig. 8).

Fig. 11 shows a Weather Shield correctly installed.

CARE INSTRUCTIONS:

Hand wash cold, hang dry, do not dry clean or iron.

LIMITED WARRANTY:

BOB Trailers Inc. takes pride in its workmanship and strives to manufacture the best products possible. Therefore, we warranty the Revolution Weather Shield against defects in material and workmanship subject to the conditions listed below. Since no product is indestructible, it does not cover defects attributable to or resulting from normal wear, abuse or alteration.

- The Revolution Weather Shield is warranted for one year from the date of original purchase.
- Warranty is only valid for the original purchaser.
- Proof of purchase is required to exercise this warranty.
- Labor and freight charges are not included.
- Normal wear, neglect, abuse, accidents, improper use are not covered by this warranty.
- Warranty claims must be made through an authorized dealer.
- This warranty is limited to the repair or replacement of the defective part. BOB shall in no event be responsible for consequential or special damages.
- This limited warranty is the only express or implied warranty applicable to BOB. Any implied warranties, including warranties of merchantability and fitness shall be limited in scope and duration in accordance with this limited warranty.